

Silver+ High Precision Digital - Coaxial 75 Ohms 4K/UHD

75 ohm coaxial video cable Silver+ for digital applications. Supports SDI transmission for 4K, 8K, UHD format and ASI signals.



TECHNICAL DATA	VK 50 Silver +	VK 60 Silver +	VK 70 Silver +	VK 75 Silver +	VK 80 Silver +	VK 90 Silver +
N. of conductors	1	1	1	1	1	1
Conductor	EHC CuAg	EHC CuAg	EHC CuAg	EHC CuAg	EHC CuAg	EHC CuAg
Galga - AWG	23	20	18	16	15	14
Stranding	Solid	Solid	Solid	Solid	Solid	Solid
Section (mm ²)	0,28	0,50	0,785	1,31	1,77	2,01
Insulation	FHDPE +	FHDPE +	FHDPE +	FHDPE +	FHDPE +	FHDPE +
Shield	Cu-Pet + Cu	Cu-Pet + Cu	Cu-Pet + Cu	AL-Pet-Al + CuSn + AL-Pet	Cu-Pet + Cu	Cu-Pet + Cu
Nominal size	4,5	5,9	7,1	8,13	9,2	10,5
Weight Kg	23,7	45	71	88	100	130
Colors						
Jacket	CMR, FRLSZH/EMC	CMR, FRLSZH/EMC	CMR, FRLSZH/EMC	CMR, FRLSZH/EMC	CMR, FRLSZH/EMC	CMR, FRLSZH/EMC
Use	Install	Install	Install	Install	Install	Install

* other options available please ask

Digital Precision - Coaxial 75 Ohms

75 ohm coaxial video cable for digital applications. Supports serial data transmission (SDI) and high definition (HDTV) and 3G-SDI TV formats.



TECHNICAL DATA	VK 2 0,4/1,95	VK 5 0,6/2,8	VK 6 0,8/3,7	VK 7 1,0/4,7
N. of conductors	1	1	1	1
Conductor	CuSn	Cu	Cu	Cu
Galga - AWG	26	23	20	18
Stranding	Solid	Solid	Solid	Solid
Section (mm ²)	0,125	0,28	0,50	0,785
Insulation	FHDPE	FHDPE	FHDPE	FHDPE
Shield	Al-Pet + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn
Nominal size	3	4,5	6	7
Weight Kg	13,6	23,7	43	56,6
Colors				
Jacket	FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH
Use	Install	Install	Install	Install

* other options available please ask

Flexible Digital Precision

75 ohm coaxial video cable for digital mobile applications. Supports serial data transmission (SDI) and high definition (HDTV) and 3G-SDI TV formats. (4K UHD).



TECHNICAL DATA	VK 66 / VK 660F	VK 680 Silver+	VK 770F ENH+	VK 780 Silver+	VK 880 Silver+
N. of conductors	1	1	1	1	1
Conductor	Cu	EHC CuAg	EHC Cu	EHC CuAg	EHC CuAg
Galga - AWG	20	20	17	17	15
Stranding	7/29	Solid	7/26	Solid	Solid
Section (mm ²)	0,43	0,50	0,88	1,13	1,77
Insulation	FHDPE	FHDPE+	FHDPE+	FHDPE+	FHDPE+
Shield	CuSn + CuSn	CuSn + CuSn	CuSn + CuSn	CuSn + CuSn	CuSn + CuSn
Nominal size	6,14	6,14	7,5	7,40	9,4
Weight Kg	70	70	80	100	130
Colors	●	● ● ●	●	●	●
Jacket	PTC / CMR	PTC / CMR	PTC / CMR	PTC / CMR	PTC / CMR
Use	Mobile	Mobile	Mobile	Mobile	Mobile

* other options available please ask

Digital Multicore

Analogue/digital video cable for typical video projection, computer, etc applications. High quality. RGBHV + components RGB/Y, R-Y, B-Y/Y, Pb, Pr/Y, Cb, Cr. Superflexible.



TECHNICAL DATA	VK 3065	VK 4065	VK 5065	VK 6065	VK 8065	VK 10065
Nº de coaxiales	0,6/2,8 x 3	0,6/2,8 x 4	0,6/2,8 x 5	0,6/2,8 x 6	0,6/2,8 x 8	0,6/2,8 x 10
Conductor	Cu	Cu	Cu	Cu	Cu	Cu
Galga - AWG	23	23	23	23	23	23
Stranding	Solid	Solid	Solid	Solid	Solid	Solid
Section (mm ²)	0,28	0,28	0,28	0,28	0,28	0,28
Insulation	FHDPE	FHDPE	FHDPE	FHDPE	FHDPE	FHDPE
Shield	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn
Nominal size	11,5	13,3	14,1	17,9	16,9	20,9
Weight Kg	172	222	247	357	386	460
Colors	●	●	●	●	●	●
Jacket	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH
Use	Install	Install	Install	Install	Install	Install

* other options available please ask

Digital Multicore




TECHNICAL DATA	VK 2378	VK 5378	VK 8376	VK 2471	VK 5471	VK 10471
Nº de coaxiales	0,8/3,7 x 2	0,8/3,7 x 5	0,8/3,7 x 8	1,0/4,7 x 2	1,0/4,7 x 5	1,0/4,7 x 10
Conductor	Cu	Cu	Cu	Cu	Cu	Cu
Galga - AWG	20	20	20	18	18	18
Stranding	Solid	Solid	Solid	Solid	Solid	Solid
Section (mm ²)	0,5	0,5	0,5	0,785	0,785	0,785
Insulation	FHDPE	FHDPE	FHDPE	FHDPE	FHDPE	FHDPE
Shield	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn	Al-Pet-Al + CuSn
Nominal size	15	18,6	24	16,2	22,1	35,5
Weight Kg	185	375	578	296	508	1157
Colors	●	●	●	●	●	●
Jacket	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC, FRLSZH	PTC / NBR	PTC, FRLSZH
Use	Install	Install	Install	Install	Install	Install

* other options available please ask



Digital Multicore Minicoaxial

Cable mainly used for professional Y/C - RGHBV applications and for miniature audio, video and control applications.



TECHNICAL DATA	VK 200		VK 420		VK 500		VK 520		VK 540	
	Coax Video		Coax Video	Signal Cable	Coax Video		Coax Video	Signal Cable	Coax Video	Signal Cable
N. of conductors	2		4	5	5		5	5	5	5
Conductor	CuSn		CuSn	CuSn	CuSn		CuSn	CuSn	CuSn	CuSn
Galga - AWG	28		28	26	28		28	26	26	26
Stranding	7/36		7/36	7/34	7/36		7/36	7/34	Solid	7/34
Section (mm ²)	0,08		0,08	0,0123	0,08		0,08	0,123	0,125	0,123
Insulation	PEX		PEX	PEX	FHDPE		FHDPE	FRLSZH	FHDPE	FRLSZH
Shield	CuSn		CuSn	CuSn	CuSn		CuSn	-	CuSn	-
Nominal size	6,8		8		9		9,5		10	
Weight Kg	50		83		93		107		135	
Colors	● ●		●		●		●		●	
Jacket	PTC / NBR		PTC, FRLSZH		PTC		PTC, FRLSZH		FRLS, FRLSZH	
Use	Mobile		Mobile		Mobile		Mobile		Mobile	

* other options available please ask

Apto también para aplicaciones analógicas

Parallel

Parallel video and audio cable. Flexible. High quality.



TECHNICAL DATA	VK 11		VK 12	
	Coax Video	Coax Audio	Coax Video	Coax Audio
N. of conductors	1	1	1	2
Conductor	CuSn	CuSn	CuSn	CuSn
Galga - AWG	28	28	28	28
Stranding	7/36	7/36	7/36	7/36
Section (mm ²)	0,08	0,08	0,08	0,08
Insulation	PPEX	PE	PEX	PE
Shield	CuSn	CuSn	CuSn	CuSn
Nominal size	6,5 x 3,5		9,5 x 3,5	
Weight Kg	31		43	
Colors	●		●	
Jacket	PTC, FRLSZH		PTC, FRLSZH	
Use	Mobile		Mobile	

* other options available please ask

Multicore Audio, Video & Signal

Cable composed of video, audio, control for several applications. 75 ohm video cable (VK1). Superflexible.



TECHNICAL DATA	VK 111			VK 112		VK 221		
	Coax Video	Coax Audio	Signal Cable	Coax Video	Signal Cable	Coax Video	Coax Audio	Signal Cable
N. of conductors	1	1	1	1	2	2	2	1
Conductor	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn
Galga - AWG	28	28	26	28	22	28	28	26
Stranding	7/36	7/36	7/34	7/36	7/30	7/36	7/36	7/34
Section (mm ²)	0,08	0,08	0,15	0,08	0,34	0,08	0,08	0,123
Insulation	FHDPE	PE	PTC	PEX	PTC	PEX	PE	PTC
Shield	CuSn	CuSn	-	CuSn	-	CuSn	CuSn	-
Nominal size	5,2			5,5		8		
Weight Kg	34			39		89		
Colors	●			●		●		
Jacket	PTC, FRLSZH			PTC		PTC, FRLSZH		
Use	Mobile			Mobile		Mobile		

* other options available please ask

Multicore Audio, Video & Signal



TECHNICAL DATA	VK 240			VK 341			VK 241		
	Coax Video	Coax Audio	Signal Cable	Coax Video	Star-Quad Audio	Signal Cable	Coax Video	Star-Quad Audio	Signal Cable
N. of conductors	2	4	1	3	1	1	3	1	9
Conductor	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn	CuSn
Galga- AWG	28	28	26	28	24	26	28	24	26
Stranding	7/36	7/36	7/34	7/36	7/32	7/34	7/36	7/32	7/34
Section (mm ²)	0,08	0,08	0,123	0,08	0,22	0,123	0,08	0,22	0,123
Insulation	FHDPE	PE	PTC	PEX	PTC	PTC	FHDPE	PTC	PTC
Shield	CuSn	CuSn	-	CuSn	Al-Pet	-	CuSn	Al-Pet	-
Nominal size	9			10,5			9,95		
Weight Kg	121			140			137		
Colors									
Jacket	PTC, FRLSZH			PTC, FRLSZH			PTC, FRLSZH		
Uso (Tipo instalación)	Mobile			Mobile			Mobile		

* other options available please ask