

## CK Series - Li Y(St)CY AWG28 80 pF/m

Multicore shielded control cable with 0.22mm<sup>2</sup> section with double general shield, designed for all kind of control applications. Perfect for mobile applications



TECHNICAL DATA	CK 6008	CK 9008	CK 12008
N. of conductors	6	9	12
Conductor	Cu	Cu	Cu
Galga - AWG	28	26	26
Stranding	7/36	7/36	7/36
Section (mm <sup>2</sup> )	0,08	0,08	0,08
Insulation	PTC	PE	PTC
Shield	Al-Pet + CuSn + Drain Wire	Al-Pet + CuSn + Drain Wire	Al-Pet + CuSn + Drain Wire
Nominal size	5,6	6,5	7
Weight	40	50	65
Colors	●	●	●
Jacket	PTC	PTC, FLRSZH	PTC
Use	Mobile	Mobile	Mobile

\* other options available please ask

## CK Series - Li 02YS(St)Y AWG28 60 pF/m

Miniature low capacitance shielded control cable with 0.123 mm<sup>2</sup> section. Perfect for computer, instrumentation or control applications such as RS-232c (null modem cable), RS 485 and RS 422.



TECHNICAL DATA	CK 2014
N. of pairs	2
Conductor	CuSn
Galga - AWG	28
Stranding	7/34
Section (mm <sup>2</sup> )	0,123
Insulation	PEX
Shield	Al-Pet (100)
Nominal size	4,9
Weight	21
Colors	●
Jacket	PTC, FRLSZH
Use	Install

\* other options available please ask