

# uniCOS F/MM 7

## uniCOS 7" Flushmount Multimedia Unit



### Description

uniCOS F/MM7 is Televic's multimedia conferencing unit, specifically designed for the Plixus architecture. Power is delivered over the Plixus conference network, therefore no need for additional power distribution towards the room. The uniCOS F/MM7 is a flushmount unit which you can configure as either a delegate or a chairman unit, which eliminates the need for different devices.

Every participant has access to all audible and visual information on his or her proper uniCOS unit.

Participants can speak, see, hear, and interact with delegate stations by combining video, audio, and document sharing.

uniCOS F/MM7 features a bright 7" touch screen which gives participants intuitive access to every uniCOS feature. From video selection, over messaging and talking to other participants, agendas, delegate information, texting, to voting, and the option to hide features that are not relevant to the meeting. With the integrated camera, you can easily configure talking heads.

### Features

The uniCOS flushmount unit features the following functionality:

- » Connected to interchangeable Plixus ports. No dedicated IN and OUT ports
- » Daisy chain or closed loop using Cat 5e / Cat 6 cable
- » 7" capacitive touch screen
- » Integrated 5MP camera providing live video of the last active speaker
- » Units configurable as delegate or chairman
- » Onscreen Priority and next button for delegate microphone control
- » Six low-latency video streams with a latency lower than 1 frame
- » Televic's "Rich Sound Processing" resulting in a crisp and clear sound that is also warm and human
- » Microphone activation button
- » Configurable LED color for microphone status (red / green)
- » Screw-lock microphone connector. Microphones sold separately.

**D-MIC30SL** **71.98.0053**

**D-MIC40SL** **71.98.0054**

**D-MIC50SL** **71.98.0055**

<b>D-MIC70SL</b>	<b>71.98.0057</b>
<b>D-MIC40FF</b>	<b>71.98.0059</b>
<b>D-MIC40BC Cardioid</b>	<b>71.98.0072</b>
<b>D-MIC40BC Hypercardioid</b>	<b>71.98.0073</b>

- » RFID card reader for authentication, with support for Mifare Classic & DESfire
- » Build-in loudspeaker, automatically muted when microphone is active
- » 3.5 mm stereo headphone connector
- » Volume and language selection on touchscreen
- » 2 USB 2 connectors to connect to for example a nameplate or charge smartphones
- » Active Speaker / Request and Reply list overview
- » Overview of participants and biography
- » Consulting agenda and meeting information
- » Speech time progress bar
- » Voting and voting result visualization (CoCon Voting required)
- » Documentation view (CoCon Documentation license required)
- » Messaging (CoCon Messaging & Services required)
- » Service request (CoCon Messaging & Services required)
- » Option to force all units to display a selected application or function and lock the view
- » Possibility to set, add, modify and time agenda items
- » Option to set up intercom calls (CoCon Intercom Required)

## Software

To fully configure, manage, and use the unit, Televic's CoCon management software has several licenses to enable specific functionality on uniCOS multimedia units:

<b>CoCon Discussion</b>	<b>71.98.1101</b>
<b>CoCon Voting</b>	<b>71.98.1104</b>
<b>CoCon Authentication</b>	<b>71.98.1105</b>
<b>CoCon Documentation</b>	<b>71.98.1109</b>
<b>CoCon Messaging &amp; Services</b>	<b>71.98.1110</b>
<b>CoCon Video Routing</b>	<b>71.98.1113</b>
<b>CoCon Intercom</b>	<b>71.98.1115</b>

## Certification

Region	Certification
Europe	CE

## Specifications

Mechanical	
Material	Brushed Aluminum
Color	Black
Size (mm)	295 (w) × 50 (h) × 135 (d)
Size packed (mm)	415 (w) × 60 (h) × 185 (d)
Weight	1200 g
Weight packed	1500 g
Electrical	
Voltage	48 VDC

Continuous output current	2 A (per port)
Power consumption (with front USB port in use)	12 W (Additional 2.5W when using the second USB port)
Power Connector	Snap and lock mini DIN power plug
Card reader	ISO 14443 MIFARE Card Reader DESfire support
USB port current	0.5 A
USB port voltage	5 V

### Display

Size	7" diagonal
Active area	153.6 × 90 mm
Refresh rate	60 Hz
Screen resolution	1024 × 600
Viewing angle	80° (Left), 80° (Right), 80° (Top), 80° (Bottom)
Luminance	560 cdm <sup>2</sup>
Technology type	IPS
Touch technology	PCT (Projective Capacitive Touch)

### Camera

Resolution	5 MP
Hierarchical degree of visibility (HDoV)	60°
Camera mode	1080p @ 30 fps

### Speaker Output

Maximum output power	1.3 W (Zload 8 Ohm)
Frequency response	200-20,000 Hz (-3 dB)
Dynamic range	97 dB / 102 dBA
THD @ nominal level	< 0.1% (@ -20 dBFS)
Load impedance	4 Ω

### Headphone Output

Maximum output	37 mW (Zload 32 Ohm)
Frequency response	22-22,000 Hz (-3 dB)
Dynamic range	94 dB / 97 dBA
THD @ nominal level	< 0.05% (@ -20 dBFS)
Load impedance	16-32 Ω

### Microphone Input

Dynamic range	> 90 dB
Frequency response	20-20,000 Hz (-3 dB)
THD @ nominal level	0.1%

### Environmental

Operating temperature	0 – 45°C
Storage and transport temperature	-20 – 70°C
Humidity	<95%, >5%

# Technical Drawing

